

GPS CONNECTION
CELLULAR CONNECTION
OBD CONNECTION



ODO25

1 STANDARD CONTENTS

ODO25

OBD-II cigarette lighter adapter (12V)

2 INSTALLING ODO25

There are two options.

1 With the adapter provided
Plug in the ODO25 with the OBD-II cigarette lighter adapter provided (12V).

Note: Idle time is not supported with the cigarette lighter adapter.

2 Directly into the OBD-II outlet

1. Locate the OBD-II outlet. The location may vary for different manufacturers, models, and production years.
2. Carefully insert the ODO25 into the OBD-II outlet.

WARNING:

- ▶ Might not be compatible with certain vehicle models. Check with your dealer.
- ▶ ODOTRACK cannot be held liable for any problems caused by connecting the device directly or incorrectly.
- ▶ If you plan to not use your vehicle for longer than a week, it is strongly recommended to remove your ODOTRACK device from your vehicle in order to keep the battery from running down needlessly.

3 SET-UP

- ▶ If the device is installed correctly, you'll see the power lights of the GPS connection and cellular connection blink (for about 1 second).

4 CONFIRMATION

- ▶ Log in to your account (odotrack.ca)
- ▶ Select the ODOtrace module
- ▶ Confirm your vehicle's location

Wait about 5 minutes after installing a new device for it to start transmitting its position.

5 LOOK UP YOUR TRIPS

- ▶ Visit the online ODOTRACK application at www.odotrack.ca/login to finish activation and to view or print your trip reports.
NOTE: The password is case-sensitive.

E-mail:

Password:

Then click the **Log in** button

6 DOWNLOAD THE ODOhybrid APP

- ▶ Optimize your experience with the ODOhybrid app available in the Apple Store and Google Play. This app lets you interact with your ODO25 device. It also allows you to edit your current trip information in real time.

7 ODOconstruction CLIENTS

- ▶ Confirm your worksites via the mobile website at c.odotrack.ca.